31.80311.21

Free-running hinge EVO EV 835E50 SOL

Material:	aluminium
Finish:	chrome effect
Mounting:	glass/glass, DIN right
Glass thickness:	8 - 19 / 21.52 mm
Sales unit (SU):	St
Unit package:	1.00
Carrying capacity:	100 kg/pair

WITHOUT hydraulics, opening angle 180°, min. door width 800 mm, max. door width 1000 mm. Can be used in combination with hydraulic hinge EVO EV 835E50 or EV 835E51 if a smaller or lighter hydraulic door is required or if the design of EVO EV 835E50 or EV 835E51 is to be adopted, but not the hydraulic function. The hinge has a pre-tension, therefore a closing stop is required


4 (3/16")
5 (3/16")
85 (3 3/8")
85 (3 3/8")
5 (3/16")


83 (3 1/4") MIN
44,5 (1 3/4")
44,5 (1 3/4")
45 (1 3/4")
22 (7/8")
50 (2")
Ø 20 (13/16")
22 (7/8")
45 (1 3/4")
150 (5 15/16") MIN


50 (2")
23
(15/16")
23
(15/16")
4
(3/16")
8÷21,52
(5/16 to 7/8")
25,1 (1")
Ø 28 (1 1/8")